

Cypress Computer Systems - Security & Data

Suprex® Wired Reader Extenders

Part Number	Description	Avail.	Category	min	UPC	SRP
SPX-1300	SUPREX® for Wiegand, Magnetic Stripe ... (24 to 200 bit) formats. RS-485 (twisted pair) communication link. Includes remote and central unit - Overall dimension each unit 4.25" x 3" x .75" (approx) 8 - 16 VDC required. Durable aluminum housing.	Stock	SUPREX®	1	816684003042	560.00
SPX-1300-BRD	SUPREX® for Wiegand, Magnetic Stripe ... (24 to 200 bit) formats. RS-485 (twisted pair) communication link. Includes remote and central unit - Overall dimension each unit 4.25" x 3" x .75" (approx) 8 - 16 VDC required. No Enclosure.	Stock	SUPREX®	1	816684007866	520.00
SPX-1300R	SUPREX® for Wiegand, Magnetic Stripe ... (24 to 200 bit) formats. RS-485 (twisted pair) communication link. Includes remote unit - Overall dimension each unit 4.25" x 3" x .75" (approx) 8 - 16 VDC required. Durable aluminum housing.	Stock	SUPREX®	1	816684001628	285.00
SPX-1300C	SUPREX® for Wiegand, Magnetic Stripe ... (24 to 200 bit) formats. RS-485 (twisted pair) communication link. Includes central unit - Overall dimension each unit 4.25" x 3" x .75" (approx) 8 - 16 VDC required. Durable aluminum housing.	Stock	SUPREX®	1	816684001642	285.00
SPX-7500	Single Door/Gate Supervised Reader Extender - RS-232/485 - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684003240	610.00
SPX-7500-BRD	Single Door/Gate Supervised Reader Extender - RS-232/485 - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Supports EXP-2000 units for additional wiegand based doors and gates. No Enclosure	Stock	SUPREX®	1	816684007736	570.00
SPX-7500R	Single Door/Gate Supervised Reader Extender - RS-232/485 - Includes remote unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001659	315.00
SPX-7500C	Single Door/Gate Supervised Reader Extender - RS-232/485 - Includes central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001666	315.00
SPX-7200	Single Door/Gate Supervised Reader Extender - Ethernet - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684003066	1,360.00
SPX-7200-BRD	Single Door/Gate Supervised Reader Extender - Ethernet - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Supports EXP-2000 units for additional wiegand based doors and gates. No Enclosure	Stock	SUPREX®	1	816684004513	1,320.00
SPX-7200R	Single Door/Gate Supervised Reader Extender - Ethernet - Includes remote unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001673	680.00
SPX-7200C	Single Door/Gate Supervised Reader Extender - Ethernet - Includes central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684005503	680.00
SPX-7400	Single Door/Gate Supervised Reader Extender - Fiber Optic (Multi-mode) - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684003127	1,510.00
SPX-7400-BRD	Single Door/Gate Supervised Reader Extender - Fiber Optic (Multi-mode) - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Supports EXP-2000 units for additional wiegand based doors and gates. No Enclosure	Stock	SUPREX®	1	816684007996	1,470.00

SPX-7400R	Single Door/Gate Supervised Reader Extender - Fiber Optic (Multi-mode) - Includes remote unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001680	760.00
SPX-7400C	Single Door/Gate Supervised Reader Extender - Fiber Optic (Multi-mode) - Includes central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001697	760.00
SPX-7410	Single Door/Gate Supervised Reader Extender - Fiber Optic (Single mode) - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684003103	1,550.00
SPX-7410-BRD	Single Door/Gate Supervised Reader Extender - Fiber Optic (Single mode) - Includes remote and central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684007989	1,510.00
SPX-7410R	Single Door/Gate Supervised Reader Extender - Fiber Optic (Single mode) - Includes remote unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001703	810.00
SPX-7410C	Single Door/Gate Supervised Reader Extender - Fiber Optic (Single mode) - Includes central unit - overall dimension each unit 4.75" x 3" x 2" (approx) - 8 - 16 VDC required. Durable aluminum housing. Supports EXP-2000 units for additional wiegand based doors and gates	Stock	SUPREX®	1	816684001710	810.00

Suprex® Wireless Access Control - 2.4 GHz

Part Number	Description	Avail.	Category	min	UPC	SRP
SPX-5631	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - integral antenna - weatherproof IP66 rated enclosure - Channel selection and Signal Strength indicator. Includes remote and central unit - overall dimension each unit 9.25" x 7.0" x 2.25" (approx) - 5000 ft range - Requires 8 - 16 VDC - Supports EXP units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684001765	1,459.00
SPX-5631-BRD	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - integral antenna - Channel selection and Signal Strength indicator. Includes remote and central unit - overall dimension each unit 6.75" x 4.75" x 2.25" (approx) - 5000 ft range - Requires 8 - 16 VDC - Supports EXP units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available - No Enclosures	Stock	SUPREX®	1	816684007699	1,409.00
SPX-5631C	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - integral antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes wireless central unit - overall dimension wireless unit 9.25" x 7.0" x 2.25" (approx) EXP wired unit 4.25" x 3" x .75" (approx) - 5000 ft range - Requires 8 - 16 VDC -(Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684007972	750.00
SPX-5631R	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - integral antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes wireless remote unit - overall dimension wireless unit 9.25" x 7.0" x 2.25" (approx) EXP wired unit 4.25" x 3" x .75" (approx) - 5000 ft range - Requires 8 - 16 VDC -(Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684007965	750.00
SPX-5632	Dual Reader Version - Enhanced Wireless Reader Extender - wireless 2.4 GHZ - integral antenna - weatherproof IP66 rated enclosure - Channel selection and Signal Strength indicator. Includes remote and central unit - overall dimension each unit 9.25" x 7.0" x 2.25" (approx) - 5000 ft range - Requires 8 - 16 VDC - (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684005589	1,859.00

SPX-5641	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - Dipole antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes remote and central unit - overall dimension each unit 9.25" x 7.0" x 2.25" (approx) - 10000 ft range - Requires 8 - 16 VDC. - Supports EXP units for additional wiegand based doors and gate. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684001772	1,659.00
SPX-5641-BRD	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - Dipole antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes remote and central unit - overall dimension each unit 6.75" x 4.75" x 2.25" (approx) - 10000 ft range - Requires 8 - 16 VDC. - Supports EXP units for additional wiegand based doors and gate. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684007705	1,609.00
SPX-5641C	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - Dipole antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes central unit - overall dimension each unit 9.25" x 7.0" x 2.25" (approx) - 10000 ft range - Requires 8 - 16 VDC. - (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684007828	850.00
SPX-5641R	Enhanced Wireless Reader Extender - wireless 2.4 GHZ - Dipole antenna - weatherproof enclosure - Channel selection and Signal Strength indicator. - Includes remote unit - overall dimension each unit 9.25" x 7.0" x 2.25" (approx) - 10000 ft range - Requires 8 - 16 VDC. - (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684007811	850.00
RPT-5651	Wireless Repeater - wireless 2.4 GHz - dipole antenna - weatherproof enclosure - overall dimension 6.75" x 4.75" x 2.25" (approx) - Requires 8 - 16 VDC - (Uses Cypress proprietary and secure Suprex® wireless network) Compatible with all current model 2.4 GHZ wireless products. AES Available upon request	Stock	SUPREX®	1	816684003172	620.00

Suprex® Wireless Access Control - Cellular

Part Number	Description	Avail.	Category	min	UPC	SRP
SPX-8XXX	Single Supervised Reader Extender - Cellular - Includes remote and central unit - weatherproof enclosure - overall dimension each unit 6.75" x 4.75" x 2.25" - ??? range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates.	Stock	SUPREX®	1	816684003097	1,550.00
SPX-8XXX-BRD	Single Supervised Reader Extender - Cellular - Includes remote and central unit - weatherproof enclosure - overall dimension each unit 6.75" x 4.75" x 2.25" - ??? range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates. No Enclosures	Stock	SUPREX®	1	816684007637	1,500.00
SPX-8XXXR	Single Supervised Reader Extender - Cellular - Includes remote unit - weatherproof enclosure -overall dimension each unit 6.75" x 4.75" x 2.25" - ??? range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates.	Stock	SUPREX®	1	816684003158	780.00
SPX-8XXXC	Single Supervised Reader Extender - Cellular - includes central unit - weatherproof enclosure -overall dimension each unit 6.75" x 4.75" x 2.25" - ??? range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates.	Stock	SUPREX®	1	816684005534	780.00

Suprex® Wireless Access Control - 900 Mhz

Part Number	Description	Avail.	Category	min	UPC	SRP
-------------	-------------	--------	----------	-----	-----	-----

SPX-5501	Single Supervised Reader Extender - wireless 900 MHz - Dipole antenna - Includes remote and central unit - weatherproof enclosure -overall dimension each unit 6.75" x 4.75" x 2.25" - 500 ft range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684003097	1,550.00
SPX-5501-BRD	Single Supervised Reader Extender - wireless 900 MHz - Dipole antenna - Includes remote and central unit - overall dimension each unit 6.75" x 4.75" x 2.25" - 500 ft range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available - No Enclosures	Stock	SUPREX®	1	816684007637	1,500.00
SPX-5521	Single Supervised Reader Extender - wireless 900 MHz - Dipole antenna - Includes remote and central unit - weatherproof enclosure -overall dimension each unit 6.75" x 4.75" x 2.25" - 7000 ft range - Requires 8 - 16 VDC. Supports EXP-2000 units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available	Stock	SUPREX®	1	816684003158	1,570.00
SPX-5521-BRD	Single Supervised Reader Extender - wireless 900 MHz - Dipole antenna - Includes remote and central unit - overall dimension each unit 6.75" x 4.75" x 2.25" - 7000 ft range - Requires 8 - 16 VDC. - Supports EXP-2000 units for additional wiegand based doors and gates. (Uses Cypress proprietary and secure Suprex® wireless network) - AES Available - No Enclosures	Stock	SUPREX®	1	816684005534	1,520.00
RPT-5551	Wireless Repeater - 900 MHz - internal dipole antenna - weatherproof enclosure - overall dimension 6.75" x 4.75" x 2.25" (approx) - Requires 8 - 16 VDC - (Uses Cypress proprietary and secure Suprex® wireless network) Compatible with all current model 900 Mhz wireless products. (Uses Cypress proprietary and secure Suprex® wireless network) -AES Available	Stock	SUPREX®	1	816684003394	620.00

Expansion modules

Part Number	Description	Avail.	Category	min	UPC	SRP
EXP-1000	Reader expansion module - RS-485 for SIO-7300 and WMR products. Field selectable for either remote or central operation. Supports reader and 2 relays with LED, door hardware and associated I/O. 8 - 16 VDC required. Durable aluminum housing - Overall dimension 4.25" x 3" x .75" (approx).	Stock	SUPREX®	1	816684003165	290.00
EXP-1000-BRD	Reader expansion module - RS-485 for SIO-7300 and WMR products. Field selectable for either remote or central operation. Supports reader and 2 relays with LED, door hardware and associated I/O. 8 - 16 VDC required. Durable aluminum housing - Overall dimension 4.25" x 3" x .75" (approx).	Stock	SUPREX®	1	816684007781	270.00
EXP-2000	Reader expansion modules - RS-485 for SPX-7400, SPX-7200, SPX-56XX products. Includes remote and central units. Supports reader and 2 relays with LED, door hardware and associated I/O. 8 - 16 VDC required. Durable aluminum housing - Overall dimension 4.25" x 3" x .75" (approx).	Stock	SUPREX®	1	816684003233	560.00
EXP-2000-BRD	Reader expansion modules - RS-485 for SPX-7400, SPX-7200, SPX-56XX products. Includes remote and central units. Supports reader and 2 relays with LED, door hardware and associated I/O. 8 - 16 VDC required. Durable aluminum housing - Overall dimension 4.25" x 3" x .75" (approx).	Stock	SUPREX®	1	816684007842	520.00

Data Converters

Part Number	Description	Avail.	Category	min	UPC	SRP
CVX-OPTW	Opto Isolator Converter - Connect one reader to two access control panels Requires 5 VDC	Stock	Data Bender™	4	816684002564	120.00

CVX-1300	Data Format Converter - contains most common formats - see website for formats - www.cypressintegration.com - Overall dimension 4.25" x 2.75" x .5" (approx) 8 -16 VDC required.	Stock	Data Bender™	1	816684002335	350.00
CVX-1300-BRD	Data Format Converter - contains most common formats - see website for formats - www.cypressintegration.com - Overall dimension 4.25" x 2.75" x .5" (approx) 8 -16 VDC required.	Stock	Data Bender™	1	816684002427	330.00
CVX-1301	Data Format Converter - contains special formats - see website for formats - www.cypressintegration.com - Overall dimension 4.25" x 2.75" x .5" (approx) 8 -16 VDC required.	Stock	Data Bender™	1	816684002991	360.00

Data Wedges

Part Number	Description	Avail.	Category	min	UPC	SRP
WDG-5912	Universal Wiegand wedge with USB cable, and programming instructions - Overall dimension 4.5" x 2.75" x 1.25" (approx)	Stock	Wedge	1	816684006043	350.00
WDG-5929	HID Prox embedded wiegand wedge with USB cable, and programming instructions - Overall dimension 4.5" x 2.75" x 1.25" (approx). Also supports Pyramid prox and AWID prox credentials.	7	Wedge	1	816684006104	595.00
WDG-5950	GM Specific - Wiegand wedge with USB cable, and programming instructions - Overall dimension 4.5" x 2.75" x 1.25" (approx)	Stock	Wedge	1	816684006098	535.00

Reader interface w/ SDK

Part Number	Description	Avail.	Category	min	UPC	SRP
SIO-7100	NEXT GEN interface module - RS-485 - overall dimension each unit 4.25" x 3.0" x .75" (approx) - Durable aluminum enclosure - 8 - 16 VDC	Stock	SUPREX®	1	816684003073	480.00
SIO-7100-BRD	NEXT GEN interface module - RS-485 - overall dimension each unit 4.25" x 3.0" x .75" (approx) - 8 - 16 VDC - No Enclosure	Stock	SUPREX®	1	816684007729	460.00
SIO-7300	NEXT GEN interface module - TCPIP - overall dimension each unit 4.75" x 3.0" x 2.00" (approx) - Durable aluminum enclosure - 8 - 16 VDC (AES Available)	Stock	SUPREX®	1	816684003080	650.00

Custom integration Products

Part Number	Description	Avail.	Category	min	UPC	SRP
CVX-OPTS	Cypress Wiegand Intelligent Splitter - creates 2 unique wiegand outputs from single wiegand input - overall dimension each unit 4.25" x 3.0" x .75" (approx) - Durable aluminum enclosure - 8 - 16 VDC - Includes engineering fee for most applications - Engineering form must be submitted with order. Forms available at www.cypressintegration.com	14	SUPREX®	1	816684003073	975.00
CVX-OPTS-XXXXX	Cypress Wiegand intelligent splitter - requires previous XXXXX order number - Reorders Only	7	SUPREX®	1	816684005510	499.00
OSM-1000-BRD	OSDP Wiegand Interface with I/O - 12VDC - Board Only (OSM) - Secure Channel capable	Stock	Osmium™	1	816684007743	170.00

OSM-2000-BRD	OSDP Wiegand Interface with I/O - 12VDC - Board Only (RFX) - Secure Channel capable	Call	Osmium™	1	816684007767	180.00
OSM-3000	OSDP Wiegand Interface with I/O - 12 VDC - Extruded Enclosure - Secure Channel capable	Call	Osmium™	1	816684007774	209.00

Barcode scanner package with wiegand interface

Part Number	Description	Avail.	Category	min	UPC	SRP
TSP-2104	Barcode Scanner with custom protocol converter package. 8 - 16 VDC required. Converter mounted in durable aluminum housing - Overall dimension scanner 2.9"x1.9"x1.0", converter - 4.25" x 3" x .75" (approx). Includes custom wiring harness. See Documentation for standard Wiegand Conversions.	7	TSP	1	816684003509	1,390.00
TSP-3100	Barcode Laser, raster, low density, Scanner with custom protocol converter package. 8 - 16 VDC required. Converter mounted in durable aluminum housing - Overall dimension scanner 1.75"x1.75"x1.0", converter - 4.25" x 3" x .75" (approx). Includes custom wiring harness. See Documentation for standard Wiegand Conversions.	7	TSP	1	816684004612	2,890.00
TSP-3200	Dual Barcode Laser, Raster, low density Scanner with custom protocol converter package. 8 - 16 VDC required. Converter mounted in durable aluminum housing - Overall dimension scanner (each) 1.75"x1.75"x1.0", converter - 4.25" x 3" x .75" (approx). Includes custom wiring harness. See Documentation for standard Wiegand Conversions.	7	TSP	1	816684004681	4,299.00

Time Displays

Part Number	Description	Avail.	Category	min	UPC	SRP
CCK-1401	Indoor clock with 1 inch LCD digits - overall dimension 5.5" x 3.5" x 2.25" - Aluminum Enclosure	Limited Stock	Time Display Products	1	816684001130	578.00
CCK-3101	Indoor clock with 1 inch LED digits - overall dimension 5.5" x 3.5" x 2.25" - Aluminum Enclosure	Call	Time Display Products	1	TBD	590.00
CCK-3104	Indoor clock with 4 inch High intensity LED digits. (requires CCX-1250 driver) overall dimension 13.5" x 7.5" x 2.25	Stock	Time Display Products	1	816684007033	790.00
CCX-1350	Universal Clock Driver - for 3104 or 1401 - 8 - 16 VDC required. Overall dimension 4.25" x 3.0" x .75" Durable aluminum housing.	Stock	Time Display Products	1	816684007040	350.00
CCX-1351	Universal Clock Driver - for 3104 or 1401 (time zone support) 8 - 16 VDC required. Overall dimension 4.25" x 3.0" x .75" Durable aluminum housing.	Stock	Time Display Products	1	816684007064	350.00
CCX-1360	Mercury panel protocol clock driver - for 3104 - 8 - 16 VDC required. Overall dimension 4.75" x 3.0" x 2.0" Durable Aluminum Enclosure	Stock	Time Display Products	1	816684007095	450.00
CCX-1300	I-Star compatible drive for for 3104 or 1401 - 8 - 16 VDC required. Overall dimension 4.25" x 3.0" x .75" Durable aluminum housing.	Stock	Time Display Products	1	816684007071	350.00

Cypress Computer Systems - Security & Data

Wireless Handheld Reader Kits

Part Number	Description	Avail.	Category	min	UPC	SRP
HHR-3152-GY	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit with gate selection feature in dock HHR-9052-GY, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007330	4,100.00
HHR-3152-WH	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit with gate selection feature in dock HHR-9052-WH (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White	14	HHR	1	816684007347	4,100.00
HHR-3156-GY	Cypress Wireless Handheld Reader kit - (1) high/low-frequency (13.56 MHz/125 kHz) handheld reader unit with gate selection feature in dock HHR-9056-GY, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007354	4,300.00
HHR-3156-WH	Cypress Wireless Handheld Reader kit - (1) high/low-frequency (13.56 MHz/125 kHz) handheld reader unit with gate selection feature in dock HHR-9056-WH (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007361	4,300.00

HHR-3157-GY	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit with gate selection feature in dock HHR-9057-GY, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007392	4,200.00
HHR-3157-WH	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit with gate selection feature in dock, HHR-9057-WH, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007408	4,200.00
HHR-3158-GY	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit with gate selection feature in dock, HHR-9058-GY, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684001499	4,200.00
HHR-3158-WH	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit with gate selection feature in dock, HHR-9058-WH, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684001505	4,200.00
HHR-3159-GY	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit with gate selection feature in dock HHR-9059-GY, (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684002083	4,200.00

HHR-3159-WH	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit with gate selection feature in dock HHR-9059-WH (1) charger HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox.. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684002090	4,200.00
HHR-3162-GY	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit in dock HHR-9062-GY, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007279	3,600.00
HHR-3162-WH	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit in dock HHR-9062-WH, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007286	3,600.00
HHR-3166-GY	Cypress Wireless Handheld Reader kit - (1) high/low-frequency (13.56 MHz/125 kHz) handheld reader unit in dock HHR-9066-GY, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007255	3,800.00
HHR-3166-WH	Cypress Wireless Handheld Reader kit - (1) high/low-frequency (13.56 MHz/125 kHz) handheld reader unit in dock HHR-9066-WH, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007262	3,800.00
HHR-3167-GY	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit in dock HHR-9067-GY, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007378	3,700.00

HHR-3167-WH	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit in dock HHR-9067-WH, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007385	3,700.00
HHR-3168-GY	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit in dock, HHR-9068-GY, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684001512	3,700.00
HHR-3168-WH	Cypress Wireless Handheld Reader kit - (1) high-frequency (13.56 MHz) handheld reader unit in dock, HHR-9068-WH, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684001529	3,700.00
HHR-3169-GY	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit in dock HHR-9069-GY, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684002106	3,700.00
HHR-3169-WH	Cypress Wireless Handheld Reader kit - (1) low-frequency (125 kHz) handheld reader unit in dock HHR-9069-WH, (1) charger HHR-RCHL, (1) Base Unit with 1 Wiegand output HHR-6300. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR		816684002113	3,700.00
HHR-3262-GY	Cypress Wireless Handheld 2-Reader kit - (2) low-frequency (125 kHz) handheld reader units in docks HHR-9062-GY, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007293	6,100.00

HHR-3262-WH	Cypress Wireless Handheld 2-Reader kit - (2) low-frequency (125 kHz) handheld reader units in docks HHR-9062-WH, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007309	6,100.00
HHR-3266-GY	Cypress Wireless Handheld 2-Reader kit - (2) high/low-frequency (13.56 MHz/125 kHz) handheld reader units in docks HHR-9066-GY, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007316	6,400.00
HHR-3266-WH	Cypress Wireless Handheld 2-Reader kit - (2) high/low-frequency (13.56 MHz/125 kHz) handheld reader units in docks HHR-9066-WH, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007323	6,400.00
HHR-3267-GY	Cypress Wireless Handheld 2-Reader kit - (2) high-frequency (13.56 MHz) handheld reader units in docks HHR-9067-GY, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684007415	6,500.00
HHR-3267-WH	Cypress Wireless Handheld 2-Reader kit - (2) high-frequency (13.56 MHz) handheld reader units in docks HHR-9067-WH, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684007422	6,500.00

HHR-3268-GY	Cypress Wireless Handheld 2-Reader kit - (2) high-frequency (13.56 MHz) handheld reader units in docks, HHR-9068-GY, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684001536	6,500.00
HHR-3268-WH	Cypress Wireless Handheld 2-Reader kit - (2) high-frequency (13.56 MHz) handheld reader units in docks, HHR-9068-WH, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: High-frequency ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684001543	6,500.00
HHR-3269-GY	Cypress Wireless Handheld 2-Reader kit - (2) low-frequency (125 kHz) handheld reader units in docks HHR-9069-GY, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: Gray.	14	HHR	1	816684002120	6,500.00
HHR-3269-WH	Cypress Wireless Handheld 2-Reader kit - (2) low-frequency (125 kHz) handheld reader units in docks HHR-9066-WH, (2) chargers HHR-RCHL, (1) Base Unit with 2 Wiegand outputs HHR-6400. Format: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs each - Uses Cypress proprietary and secure Suprex® wireless network. Color: White.	14	HHR	1	816684002137	6,500.00
Wireless Handheld Reader Devices						
Part Number	Description				UPC	SRP
HHR-9052-GY	Cypress Wireless Handheld Reader only - Reads low-frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001147	2,900.00

HHR-9052-WH	Cypress Wireless Handheld Reader only - Reads low-frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001154	2,900.00
HHR-9056-GY	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) and low frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001185	3,200.00
HHR-9056-WH	Cypress Wireless Handheld Reader only - Reads high/low-frequency (13.56 MHz) and low frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001192	3,200.00
HHR-9057-GY	Cypress Wireless Handheld Reader only- Reads high-frequency (13.56 MHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001222	3,100.00
HHR-9057-WH	Cypress Wireless Handheld Reader only - Reads high-frequency (13.56 MHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color:White.	14	HHR	1	816684001239	3,100.00
HHR-9058-GY	Cypress Wireless Handheld Reader only- Reads high-frequency (13.56 MHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must	14	HHR	1	816684001468	3,600.00

HHR-9058-WH	Cypress Wireless Handheld Reader only- Reads high-frequency (13.56 MHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001451	3,600.00
HHR-9059-GY	Cypress Wireless Handheld Reader only - Reads low frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684002045	3,600.00
HHR-9059-WH	Cypress Wireless Handheld Reader only - Reads low-frequency (125 kHz) credentials. Handheld unit has gate/direction selection feature. Includes charging dock. Supported formats: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684002052	3,600.00
HHR-9062-GY	Cypress Wireless Handheld Reader only - Reads low-frequency (125 kHz) credentials. Includes charging dock. Supported formats: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001161	2,600.00
HHR-9062-WH	Cypress Wireless Handheld Reader only - Reads low-frequency (125 kHz) credentials. Includes charging dock. Supported formats: Farpointe Prox, HID Prox, AWID Prox (125 kHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001178	2,600.00
HHR-9066-GY	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) and low (125 kHz) frequency credentials. Includes charging dock. Supported formats: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001208	2,900.00

HHR-9066-WH	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) and low (125 kHz) frequency credentials. Includes charging dock. Supported formats: HID Prox, Indala Prox, EM4102, AWID Prox; ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001215	2,900.00
HHR-9067-GY	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) frequency credentials. Includes charging dock. Supported formats: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001246	2,800.00
HHR-9067-WH	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) frequency credentials. Includes charging dock. Supported formats: Farpointe Sector, HID iClass® CSN/UID Outputs (13.56 MHz) . AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001253	2,800.00
HHR-9068-GY	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) frequency credentials. Includes charging dock. Supported formats: ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684001482	2,800.00
HHR-9068-WH	Cypress Wireless Handheld Reader only - Reads high (13.56 MHz) frequency credentials. Includes charging dock. Supported formats: ISO14443A/B ISO15693, FeliCa™ (IDm); MIFARE Classic®, MIFARE DESFire® 0.6, MIFARE DESFire® EV1, HID: iCLASS® Standard/SE/SR/Seos; PIV II, Secure Identity Object® (SIO®). AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684001475	2,800.00
HHR-9069-GY	Cypress Wireless Handheld Reader only - Reads low (125 kHz) frequency credentials. Includes charging dock. Supported formats: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: Gray.	14	HHR	1	816684002069	2,800.00

HHR-9069-WH	Cypress Wireless Handheld Reader only - Reads low (125 kHz) frequency credentials. Includes charging dock. Supported formats: Low-frequency HID Prox, Indala Prox, EM4102, AWID Prox. AES encryption optional - 500' range - Handheld dimension 6.8" x 3.6" x 1.6", 1.0 lbs - Uses Cypress proprietary and secure Suprex® wireless network. Must be used with base unit. Color: White.	14	HHR	1	816684002076	2,800.00
HHR-6300	Base Unit with 1 Wiegand output, for Cypress Handheld Wireless Reader. Color: White.	14	HHR	1	816684001277	660.00
HHR-6400	Base Unit with 2 Wiegand outputs, for Cypress Handheld Wireless Reader. Color: White.	14	HHR	1	816684001260	900.00
HHR-DOCK-GY	Charging dock for HHR series Wireless Handheld Readers - Color Gray	14	HHR	1	816684001291	141.00
HHR-DOCK-WH	Charging dock for HHR series Wireless Handheld Readers - Color Gray	14	HHR	1	816684001307	141.00
HHR-RCHL	Power charger for HHR-DOCK. 8.4 V wall plug - Select either US, UK, EU, AU	14	HHR	1	816684001284	65.00
HHR-APCM	Cypress address programming cards for high-frequency MiFare Cypress Handheld Wireless Readers. Address Cards 0,1, 2	14	HHR	1		15.00
HHR-APCH	Cypress address programming cards for high-frequency Cypress Handheld Wireless Readers. Address Cards 0,1, 2	14	HHR	1	816684001437	15.00
HHR-APCL	Cypress address programming cards for low-frequency Cypress Handheld Wireless Readers. Address Cards 0,1, 2	14	HHR	1	816684001413	15.00
HHR-CPCM	Cypress channel programming cards for high-frequency MiFare Cypress Handheld Wireless Readers. Channel cards 2 - 14	14	HHR	1		70.00
HHR-CPCH	Cypress channel programming cards for high-frequency Cypress Handheld Wireless Readers. Channel cards 2 - 14	14	HHR	1	816684001420	70.00
HHR-CPCL	Cypress channel programming cards for low-frequency Cypress Handheld Wireless Readers. Channel cards 2 - 14	14	HHR	1	816684001406	70.00
HHR-HOL2	Belt-clip holster for Cypress Handheld Wireless Reader.	14	HHR	1	816684001444	65.00
HHR-HOL3	Shoulder holster with window for Cypress Handheld Wireless Reader. Includes adjustable shoulder strap.	14	HHR	1	816684001390	89.00